

Available Functions:

Product / Customer	Transactional	Miscellaneous
GetProductDetails	UpdateOrder	GetWarehouseList
GetProductPriceAvail	UpdateInvoice	Valid Fields and Filters
GetCustomerDetails	UpdatePurchaseOrder	
UpdateCustomerDetails	UpdateBranchTransfer	
	GetTransactionDetails	
	FilterTransactionRange	

Technical Summary

HTTP Method	POST
Request Content-Type	"application/x-www-form-urlencoded"
Response Content-Type	text/plain

Additional Notes

- Data requests are either a JSON array or a Single string field
- Data request parameter positions are fixed, use blank placeholders if "Allow Blank" is set to **Yes**
- Data parameters in body of request, not the header
- Replace following characters before all API requests (characters will be converted back once request is received)
 - Replace & with ^
 - Replace < with `
- All Error Responses start with an "!" + Error Message

Function: GetProductDetails

Get extract of Product details in a bulk method.

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Field List	<i>fields</i>	List of Product fields that can be returned. See list of valid fields	Yes	JSON
3	Filter List	<i>filter</i>	List of Product filters that can be applied. See list of valid fields	Yes	JSON
4	Warehouse	<i>wh</i>	Optional warehouse/branch code	Yes	Text
5	Prices Inc/Ex GST	<i>incexgst</i>	Selling prices to have GST Included/Excluded. Value: I = Include, X = Exclude	No	Text

Request Sample:

```
f=getProductDetails&key=12345&fields={"fields":[{"field":"descr"}, {"field":"barcode"}, {"field":"grpcode"}, {"field":"price1"}, {"field":"instqty"}, {"field":"location"}]}&filter={"filter":[{"grpcode":"ZZ", "subgroup":"YY"}]}&wh=NSW&incexgst=I
```

Result Sample:

```
{"Product":[{"part":"017800", "descr":"SYKES CYLINDER HEAD STAND", "barcode":"9644827162839", "grpcode":"ZZ", "price1":"266.38", "instqty":"","location":""}, {"part":"05-2054", "descr":"GATES LOWER RAD HOSE", "barcode":"9346827663851", "grpcode":"ZZ", "price1":"38.65", "instqty":"0", "location":""}, ..... ]}]
```

Extra Notes:

Multiple values of the same Filter field can be requested with a comma.
Eg: filter={"filter":[{"grpcode":"**XX,ZZ**", "subgroup":"YY"}]}

Function: GetProductPriceAvail

Get extract of Product details by providing specific Part Numbers.

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Part List	<i>product</i>	List of Part numbers	No	JSON
3	Field List	<i>fields</i>	List of Product fields that can be returned. See list of valid fields	Yes	JSON
4	Warehouse	<i>wh</i>	Optional warehouse/branch code	Yes	Text
5	Customer Code	<i>cust</i>	Optional Customer Code to return Customer Special Price	Yes	Text
6	Prices Inc/Ex GST	<i>incexgst</i>	Selling prices to have GST Included/Excluded. Value: I =Include, X = Exclude	No	Text

Request Sample:

```
f=getProductPriceAvail&key=12345&product={"product":[{"part":"BJ55"}, {"part":"Z9"}, {"part":"Z9Y"}]}&fields={"fields":[{"field":"grpcode"}, {"field":"descr"}, {"field":"instkqty"}, {"field":"location"}]}&wh=NSW&cust=ABC123&incexgst=I
```

Result Sample:

```
{"Product":[{"Part":"BJ55", "grpcode":"SUS", "descr":"BALL JOINT", "instkqty":"0", "location":"","ValidPart":"True", "CustomerPrice":"22"}, {"Part":"Z9", "grpcode":"RYC", "descr":"RYC-OIL FILTER ", "instkqty":"88", "location":"B1", "ValidPart":"True", "CustomerPrice":"6.6"}, {"Part":"Z9Y", "grpcode":"CHA", "descr":"CHA-CHAMPION PLUGS", "instkqty":"55", "location":"B2", "ValidPart":"True", "CustomerPrice":"5.23"}]}
```

Extra Notes:

- If Customer Code passed, then “CustomerPrice” field is returned in results.
- Field “ValidPart” (true/false) returned at all times to determine if Part Number found a match or not.

Function: GetCustomerDetails

Get extract of Customer Details.

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Customer Code	<i>custcode</i>	Unique Customer Code	No	Text
3	Field List	<i>fields</i>	List of Customer fields that can be returned. See list of valid fields	Yes	JSON

Request Sample:

```
f=getCustomerDetails&key=12345&custcode=ABC123&fields={"fields":[{"field":"name"}, {"field":"address1"}, {"field":"address2"}, {"field":"address3"}, {"field":"pcode"}]}
```

Result Sample:

```
{"Customer":{"custcode":"ABC123","name":"New Customer","address1":"Zen Building","address2":"100 Sample Street","address3":"Sydney NSW","pcode":"2100"}}
```

Function: UpdateCustomerDetails

Update Customer Details.

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Customer Code	<i>custcode</i>	Unique Customer Code (10 character limit)	No	Text
3	Field List	<i>fields</i>	List of Customer fields that can be returned. See list of valid fields	Yes	JSON
4	Update If Not Found	<i>UpdateIfNotFound</i>	True/False – flag to create customer if CustCode not found	No	Text

Request Sample:

```
f=updateCustomerDetails&key=12345&custcode=ABC123&fields={"fields":[{"name":"New Customer","address1":"Zen Building","address2":"100 Sample Street","address3":"Sydney NSW","pcode":"2100"}]}&updateifnotfound=true
```

Result Sample:

Customer Updated
or
! + Error Message

Extra Notes:

- Customer Code limit is 10 characters
- Mobile numbers make for good customer codes instead of auto generating a random code

Function: UpdateOrder / UpdateInvoice

Update Customer Order / Invoice

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Header	<i>Header</i>	List of transactional header fields that can be submitted. See list of valid fields	No	JSON
3	Products	<i>Products</i>	List of Product fields that can be submitted. See list of valid fields	No	JSON
4	Warehouse	<i>wh</i>	Warehouse/branch code	Yes	Text
5	Prices Inc/Ex GST	<i>incexgst</i>	Submitted selling prices have GST Included/Excluded. Value: I =Include, X = Exclude	No	Text

Request Sample:

Order:

```
f=updateOrder&key=12345&header={"fields":{"custcode":"ABC123","name":"New Customer","transdate":"7/05/2018","transid":"ZZZ","orderno":"XXX","address1":"Zen Building","address2":"100 Sample Street","address3":"Sydney NSW 2100","courier":"Peach Air Ways","freight":"3.30","reference":"XXX","comments":"leave package at door"}}&products={"parts":[{"part":"BJ55","qty":"1","price":"49.99"},{"part":"Z9","qty":"3","price":"19.50"},{"part":"Z9Y","qty":"9","price":"29.95"}],"note":"Optional note that may relate to the parts list"}}&wh=NSW&incexgst=I
```

Invoice:

```
f=updateInvoice&key=12345&header={"fields":{"custcode":"ABC123","name":"New Customer","transdate":"8/05/2018","transid":"ZZZ","orderno":"XXX","address1":"Zen Building","address2":"100 Sample Street","address3":"Sydney NSW 2100","courier":"Peach Air Ways","freight":"3.30","pmtmethod":"3","reference":"XXX","comments":"leave package at door"}}&products={"parts":[{"part":"Z9Y","qty":"9","price":"29.95"}]}&wh=&incexgst=I
```

Result Sample:

```
Packslip Created: COXXXXXX  
Or  
Invoice Created: IEXXXXXX  
Or  
! + Error Message
```

Extra Notes:

- Product JSON array requires: Part, Qty, individual Price
- If Warehouse left blank, transaction will be posted to the Head office branch.

Function: UpdatePurchaseOrder

Update Supplier Purchase Order – with an option to automatically email

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Header	<i>Header</i>	List of transactional header fields that can be submitted. See list of valid fields	No	JSON
3	Products	<i>Products</i>	List of Product fields that can be submitted. See list of valid fields	No	JSON
4	Email	<i>email</i>	Optional email parameter. Can just be left blank if not required. See more info	Yes	JSON
5	Warehouse	<i>wh</i>	Warehouse/branch code	Yes	Text

Request Sample:

```
f=updatePurchaseOrder&key=12345&header={"fields":[{"suppcode":"ABC123","reference":"refNo123","enterby":"JOHN","shipdate":"11/Oct/2020","comments":"Advise if cannot supply"}]}&products={"parts":[{"part":"BJ55","qty":"1"}, {"part":"Z9", "qty":"3"}, {"part":"Z9Y", "qty":"9"}]}&email={"email":{"send":"yes"}}&wharea=NSW
```

Result Sample: *both transaction ID and email status returned, joined by semicolon*

Purchase Order: SOXXXX;Email: Success
Or
! + Error Message

Extra Notes:

- Product JSON array requires: Part, Qty
- If Warehouse left blank, transaction will be posted to the Head office branch.

Function: UpdateBranchTransfer

Update Branch Transfer – with an option to automatically email

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	Header	<i>Header</i>	List of transactional header fields that can be submitted. See list of valid fields	No	JSON
3	Products	<i>Products</i>	List of Product fields that can be submitted. See list of valid fields	No	JSON
4	Email	<i>email</i>	Optional email parameter. Can just be left blank if not required. See more info	Yes	JSON

Request Sample:

```
f=updateBranchTransfer&key=12345&header={"fields":[{"fromarea":"NSW","toarea":"VIC","status":"R","reference":"refNo123","orderno":"ordNo899","comments":"Advise if cannot supply"}]}&products={"parts":[{"part":"BJ55","qty":"1"}, {"part":"Z9","qty":"3"}, {"part":"Z9Y","qty":"9"}]}&email={"email":{"send":"yes"}}
```

Result Sample: *both transaction ID and email status returned, joined by semicolon*

Branch Transfer: BTXXXX;Email: Success

Or

! + Error Message *(if transaction failed to generate)*

Extra Notes:

- Product JSON array requires: Part, Qty
- Status field in header can be **R** = Original Request (*default*) or **T** = In Transit or **F** = Finalise

Function: GetTransactionDetails

Get header and Product details based on a single Transaction ID.

For more multiple transaction results see function: **FilterTransactionRange**

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	TrnType	<i>trntype</i>	Either CO = Order IE = Invoice – if blank, then prefix TransID with trntype.	Yes	Text
3	TransID	<i>transid</i>	Transaction ID – usually numeric. Can be: CO#### or IE#### or just ### if trntype provided	No	Text
4	Split Results	<i>split</i>	Split results into 2 objects – Header / Details. Reduces unnecessary repeated data.	No	Yes/No

Request Sample:

```
f=getTransactionDetails&key=12345&trntype=CO&transid=CO50724&split=yes
```

Result Sample (Split):

```
{
  "Header": {
    "id": "CO50724",
    "custcode": "ABC123",
    "billto": "ABC123",
    "duedate": "13/05/2020",
    "name": "New Customer",
    "orderno": "TEST",
    "invno": "",
    "packslip": "50724",
    "reference": "",
    "area": "WH002",
    "subtotal": "110.22",
    "freight": "2.73",
    "gst": "11.29",
    "total": "124.24",
    "pmtmethod": "",
    "salesman": "MAX",
    "items": "3",
    "message": "Comments: leave package at door [TransID: ZZZ] [TransDate: 20/05/2020]",
    "courier": "Peach Air Ways",
    "address1": "Zen Building",
    "address2": "100 Sample Street",
    "address3": "Sydney NSW 2100",
    "delnme": "",
    "delad1": "",
    "delad2": "",
    "delad3": "",
    "internet": "abc@domain.com",
    "salesemail": "",
    "accountsemail": ""
  },
  "Details": [
    {
      "lne": "1",
      "id": "CO50724",
      "part": "BJ55",
      "desc": "Holden 55-80 Lower Ball Joint",
      "ord": "3",
      "supp": "3",
      "price": "22.5",
      "nett": "67.5"
    },
    {
      "lne": "2",
      "id": "CO50724",
      "part": "Z9",
      "desc": "Oil Filter",
      "ord": "5",
      "supp": "5",
      "price": "7.88",
      "nett": "39.4"
    },
    {
      "lne": "3",
      "id": "CO50724",
      "part": "Z9Y",
      "desc": "Champion Marine/Mcycle Spark Plug",
      "ord": "1",
      "supp": "1",
      "price": "14.34",
      "nett": "14.34"
    }
  ]
}
```

Result Sample (Combined):

```
{
  "Transaction": [
    {
      "id": "CO50724",
      "custcode": "ABC123",
      "billto": "ABC123",
      "duedate": "13/05/2020",
      "name": "New Customer",
      "orderno": "TEST",
      "invno": "",
      "packslip": "50724",
      "reference": "",
      "area": "WH002",
      "subtotal": "110.22",
      "freight": "2.73",
      "gst": "11.29",
      "total": "124.24",
      "pmtmethod": "",
      "salesman": "MAX",
      "items": "3",
      "message": "Comments: leave package at door [TransID: ZZZ] [TransDate: 20/05/2020]",
      "courier": "Peach Air Ways",
      "address1": "Zen Building",
      "address2": "100 Sample Street",
      "address3": "Sydney NSW 2100",
      "delnme": "",
      "delad1": "",
      "delad2": "",
      "delad3": "",
      "lne": "1",
      "part": "BJ55",
      "desc": "Holden 55-80 Lower Ball Joint",
      "ord": "3",
      "supp": "3",
      "price": "22.5",
      "nett": "67.5",
      "internet": "abc@domain.com",
      "salesemail": "",
      "accountsemail": ""
    },
    {
      "id": "CO50724",
      "custcode": "ABC123",
      "billto": "ABC123",
      "duedate": "13/05/2020",
      "name": "New Customer",
      "orderno": "TEST",
      "invno": "",
      "packslip": "50724",
      "reference": "",
      "area": "WH002",
      "subtotal": "110.22",
      "freight": "2.73",
      "gst": "11.29",
      "total": "124.24",
      "pmtmethod": "",
      "salesman": "MAX",
      "items": "3",
      "message": "Comments: leave package at door [TransID: ZZZ] [TransDate: 20/05/2020]",
      "courier": "Peach Air Ways",
      "address1": "Zen Building",
      "address2": "100 Sample Street",
      "address3": "Sydney NSW 2100",
      "delnme": "",
      "delad1": "",
      "delad2": "",
      "delad3": "",
      "lne": "2",
      "part": "Z9",
      "desc": "Oil Filter",
      "ord": "5",
      "supp": "5",
      "price": "7.88",
      "nett": "39.4",
      "internet": "abc@domain.com",
      "salesemail": "",
      "accountsemail": ""
    },
    {
      "id": "CO50724",
      "custcode": "ABC123",
      "billto": "ABC123",
      "duedate": "13/05/2020",
      "name": "New Customer",
      "orderno": "TEST",
      "invno": "",
      "packslip": "50724",
      "reference": "",
      "area": "WH002",
      "subtotal": "110.22",
      "freight": "2.73",
      "gst": "11.29",
      "total": "124.24",
      "pmtmethod": "",
      "salesman": "MAX",
      "items": "3",
      "message": "Comments: leave package at door [TransID: ZZZ] [TransDate: 20/05/2020]",
      "courier": "Peach Air Ways",
      "address1": "Zen Building",
      "address2": "100 Sample Street",
      "address3": "Sydney NSW 2100",
      "delnme": "",
      "delad1": "",
      "delad2": "",
      "delad3": "",
      "lne": "3",
      "part": "Z9Y",
      "desc": "Champion Marine/Mcycle Spark Plug",
      "ord": "1",
      "supp": "1",
      "price": "14.34",
      "nett": "14.34",
      "internet": "abc@domain.com",
      "salesemail": "",
      "accountsemail": ""
    }
  ]
}
```

Function: FilterTransactionRange

Get Customer/Supplier and Product Transactional details based on a Date and Transaction Type and other optional filters.

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	<i>key</i>	Unique Connection Key – will be provided by Peach Software Support	No	Text
2	TrnType	<i>trntype</i>	Either CO = Order IE = Invoice SO = Supplier Order	No	Text
3	Filter Date	<u><i>transdate</i></u>	Filter transaction date, format either: dd/MM/yyyy -or- dd/MMM/yyyy <i>If left blank, results will be limited to the first 100 records using other filters provided.</i>	Yes	Date
4	Header Fields	<i>headfld</i>	List of Header fields that can be returned. See list of valid fields	No	JSON
5	Product Fields	<i>stkfld</i>	List of Product fields that can be returned. See list of valid fields	Yes	JSON
6	Filter	<i>filter</i>	List of Header filters that can be applied. See list of valid fields	Yes	JSON
7	Nest results	<i>nest</i>	Nest the Product data within each header. Reduces unnecessary repeated header data.	No	Yes/No

Request Sample:

```
f=filtertransactionrange&key=12345&trntype=IE&transdate=01/Jan/2020&headfld={'fields': [{'field': 'id'}, {'field': 'name'}, {'field': 'address1'}, {'field': 'address2'}, {'field': 'address3'}, {'field': 'items'}, {'field': 'total'}]}&stkfld={'fields': [{'field': 'lne'}, {'field': 'part'}, {'field': 'desc'}, {'field': 'ord'}, {'field': 'supp'}]}&filter={'filter': [{'courier': 'FASTWAYS', 'TNT AUTO', 'salesman': 'JOHN'}]}&nest=true
```

Extra Notes:

Multiple values of the same Filter field can be requested with a comma.
Eg: `filter={"filter": [{"courier": "FASTWAYS", "TNT AUTO"}]}`

Function: GetWarehouseList

Get Warehouse/Branch listing – includes warehouse address and contact info if set.

Pos	Summary	Place holder	Comment	Allow Blank	Type
1	Connection Key	key	Unique Connection Key – will be provided by Peach Software Support	No	Text

Request Sample:

```
f=getWarehouseList&key=12345
```

Result Sample:

```
{"Warehouse":[{"area":"WH002","name":"Warehouse 2","branchname":"Warehouse 2","branchaddress1":"Unit 67, 213 Old bridge Road","branchaddress2":"Moorebank","branchaddress3":"NSW, 2170","branchphone":"02 9876-4321","branchfax":"02 9876-4399","branchemail":"wh2@domain.com","isprimary":"True"}, {"area":"WH003","name":"Warehouse 3","branchname":"Warehouse 3","branchaddress1":"23-45 Jordan Way","branchaddress2":"Wetherill Park","branchaddress3":"NSW 2164","branchphone":"02 8192-9384","branchfax":"","branchemail":"wh3@domain.com","isprimary":"False"}, {"area":"WH005","name":"Warehouse 5","branchname":"Warehouse 5","branchaddress1":"84-98 Bulls Point Road","branchaddress2":"Castle Hill","branchaddress3":"NSW 2154","branchphone":"02 4918-7364","branchfax":"02 4918-7000","branchemail":"wh5@domain.com","isprimary":"False"}]}
```

Other: Valid Product / Warehouse Fields and Filters

Get Data - Products Fields

Part	Promo1	FutStartDt	SalQtyYtd	FSaleDate	Labline2	PQty4	STUpdated
Descr	Promo2	LastCost	PurQtyYtd	LSaleDate	Labline3	Pqty5	LastModified
BarCode	Promo3	AveCost	SalQtyLy	Notes	Labline4	Pqty6	PriceList
GrpCode	Promo4	CurrCost	PurQtyLy	PrefSupp	Specs1	AveSale	SuppOrdDate
Price1	Promo5	FutCost	InStkQty	Active	Specs2	FixPrice	Brand
Price2	ProStDate	Duty	MinLvlQty	Markup	Specs3	CreateDate	PriceFRetail
Price3	ProFinDate	Weight	MaxLvlQty	CodeField	UnitSale	Promo6	Core
Price4	Future1	Location	CustOrdQty	UnitQty	PrefSupp2	Future6	Ave3Month
Price5	Future2	OEM	SuppOrdQty	PackSize	KitManual	LabRetail	Ave6Month
Price6	Future3	SubGroup	BkOrdQty	Volume	PQty1	Zerostock	Ave9Month
PriceLvl	Future4	SalQtyMtd	FPurDate	Deposit	PQty2	Tag	Ave12Month
TaxCode	Future5	PurQtyMtd	LPurDate	Labline1	PQty3	Category	DGCode

Get Data - Warehouse / Branch Product Fields

Area	MaxLvlQty	SalQtyM2	PurQtyLY	FSaleDate	SuppordDate	STUpdated
InStkQty	UseQtyMtd	SalQtyM3	UseQtyYtd	LSaleDate	LocalQty	Ave3Month
SalQtyMtd	SalQtyYtd	AveSale	UseQtyLy	CustOrdQty	LocalVal	Ave6Month
PurQtyMtd	Location	TotSale	FPurDate	SuppOrdQty	JCOrdQty	Ave9Month
MinLvlQty	SalQtyM1	SalQtyLY	LPurDate	BkOrdQty	JCOrdVal	Ave12Month

Filter Data - Product

GrpCode	SubGroup	PrefSupp	PrefSupp2	Brand	Category	CodeField	PriceList	LastModified
---------	----------	----------	-----------	-------	----------	-----------	-----------	--------------

Notes:

Multiple values of the same Filter field can be requested with a comma.

Eg: filter={"filter":[{"grpcode":"XX,ZZ","subgroup":"YY"}]}

LastModified filtering

Format: dd/MM/yyyy or dd/MMM/yyyy

Defaults to: equal to or greater than **>=** unless operator sent in request.

Eg: filter={"filter":[{"LastModified":">=dd/MMM/yyyy"}]}

Eg: filter={"filter":[{"LastModified":"=dd/MMM/yyyy"}]}

Eg: filter={"filter":[{"LastModified":"<=dd/MMM/yyyy"}]}

Other: Valid Customer Fields and Filters

Get Data - Customer Fields

CustCode	Delad3	Area	AcctNo	LastPdAmt	Budget	Cycle	CreateDate
BillTo	DelPCode	RptCode	Current	LastPdDate	CashDisc	ABN	CommRate
Name	Phone	PriceLvl	ThirtyDays	AcnNo	NoPromo	GSTExempt	
Address1	Fax	PriceAs	SixtyDays	FrtRate	Financed	LastModified	
Address2	Internet	FSale	NinetyDays	Courier	120Days	ID	
Address3	Mobile	LSale	Total	Future	MktCode	AccountsEmail	
PCode	Contact1	CrdLmt	Bank	Notes	NoFreight	SalesEmail	
Delad1	Contact2	Terms	Branch	BkOrd	Rebate	EmailInvoiceYN	
Delad2	SalesMan	BsbNo	Drawer	ChkCredit	Fee	CustomerType	

Update Data - Customer Fields

Name	Delad2	Mobile	PriceLvl	BsbNo	FrtRate	MktCode	ID
Address1	Delad3	Contact1	PriceAs	AcctNo	Courier	NoFreight	AccountsEmail
Address2	DelPCode	Contact2	FSale	Bank	Notes	Fee	SalesEmail
Address3	Phone	SalesMan	LSale	Branch	BkOrd	Cycle	EmailInvoiceYN
PCode	Fax	Area	CrdLmt	Drawer	Budget	ABN	CustomerType
Delad1	Internet	RptCode	Terms	AcnNo	Financed	GSTExempt	CommRate

Other: Transactional Fields and Filters

Update Transaction - Customer Order / Invoice Header Fields

Field	Required	Limit	Order	Invoice	Uses default if blank	Comment
CustCode	Yes	10	Yes	Yes		Customer Code
Name		40	Yes	Yes	Yes	Customer Name / Company
Address1		40	Yes	Yes	Yes	Billing Unit / Street
Address2		40	Yes	Yes	Yes	Billing City
Address3		40	Yes	Yes	Yes	Billing State and Postcode
DelNme		40	Yes	Yes	Yes	Delivery Name / Company
DelAd1		40	Yes	Yes	Yes	Delivery Unit / Street
DelAd2		40	Yes	Yes	Yes	Delivery City
DelAd3		40	Yes	Yes	Yes	Delivery State and Postcode
OrderNo	Yes	20	Yes	Yes		Customer Order Number
Courier		20	Yes	Yes		Courier if applicable
Freight		-	Yes	Yes		Freight Charge
Reference		10	Yes	Yes		Extra option from Customer, eg: Ordered By
TransID		10	Yes	Yes		Note only -- Added to Message with prefix
TransDate		-	Yes	Yes		Note only -- Added to Message with prefix
Comments		250	Yes	Yes		Message from Customer
Salesman		6	Yes	Yes		Defaults to 'API' unless supplied
DeptCode		3	Yes	Yes		Transaction Flag. Defaults to blank
SalesGLCode		10	No	Yes	Yes	Sales General Ledger code
DontAdjustStock		-	No	Yes		True/false – Set to true if ALL products on transaction if Stock Levels are Not to be adjusted.
PmtMethod (Invoices Only)	Yes	1	No	Yes		Valid Payment Types: 1 = Cash 2 = EFTPos 3 = PayPal 4 = MasterCard 5 = Visa 6 = Amex/Other 7 = Direct Payment 8 = Cheque 9 = Account

Update Transaction - Customer Order / Invoice Product Fields

Field	Mandatory	Limit	Comment
Part	Yes	20	Part Number – will be validated when processing transaction
Qty	Yes	-	Transaction Quantity. Negative qty's will be treated as credit note.
Price	Yes	-	Single Unit price, should always be positive value.
Note		80	Comment line – leave all other fields blank when adding a line note.

Get Data – Transaction: Customer Order/Invoice Header Fields

ID	Name	CustCode	BillTo	OrderNo	PackSlip	Area	TrnType
SubTotal	GST	Freight	Total	Paid	UnPaid	PmtMethod	Items
Cartons	Connote	Weight	PackedBy	CheckedBy	Address1	Address2	Address3
Date	DueDate	InvNo	Reference	BatchNo	TransTime	Internet	DeptCode
Message	Salesman	ShipDate	Courier	DelNme	Delad1	Delad2	Delad3
SuppCode							

Get Data – Transaction: Customer Order/Invoice Product Details Fields

Lne	ID	Part	Desc	Ord	Supp	BkOrd	RefPrice	Location
Price	Nett	GST	SuppPart	Disc	DueDate	GrpCode	SubGroup	ShipDate

Filter Data - Transaction: Customer Order/Invoice Header Fields

ID	CustCode	BillTo	OrderNo	PackSlip	Area	TrnType	BatchNo	CheckedBy
PmtMethod	InvNo	Reference	DeptCode	Salesman	Courier	Connote	PackedBy	SuppCode

Email JSON Structure

Currently only an option when processing a Supplier Purchase Order or a Branch Transfer.

If parameter is blank in request, it will default to **send = No**

Otherwise see structure highlighted below to create a successful email request.

The JSON object is being used as future updates will allow for other parameters, *eg: CC, BCC, Subject plus more...*

For now, the email will be sent to the linked email addresses for either the Supplier or FromArea Branch.

Sample:

```
f=updateBranchTransfer&key=12345&header={"fields":{"fromarea":"NSW","toarea":"VIC","status":"R","reference":"refNo123","orderno":"ordNo899","comments":"Advise if cannot supply"}}&products={"parts":{"part":"BJ55","qty":"1"},"part":"Z9","qty":"3"},"part":"Z9Y","qty":"9"}}&email={"email":{"send":"yes"}}
```

Result Sample: When emailing is available, then the results returned are both the transaction ID and email status, joined by semicolon. Here are some samples of possible results:

```
Branch Transfer: BTXXXX;Email: Not Requested
Or
Branch Transfer: BTXXXX;Email: !Failed to send: reason why
Or
Branch Transfer: BTXXXX;Email: Success
Or
! + Error Message (if transaction failed to generate)
```

Update Transaction – Supplier Purchase Order

Field	Mandatory	Limit	Uses default if blank	Comment
Header Fields				
SuppCode	Yes	10		Supplier Code
Name		40	Yes	Supplier Name
DelNme		40	Yes	Delivery Name
DelAd1		40	Yes	Delivery Unit / Street
DelAd2		40	Yes	Delivery City
DelAd3		40	Yes	Delivery State and PostCode
OrderNo		20		Order Number
Reference		10		Reference Number
TransID		10		Note only -- Added to Message with prefix
TransDate		dd/MMM/yyyy		Note only -- Added to Message with prefix
Comments		250		Message for Supplier
EnterBy		10		Order Entered by
ShipDate		dd/MMM/yyyy		Ship Date that order is expected to arrive
Product Fields				
Part	Yes	20		Primary Part Number
Qty	Yes	-		Order Qty (<i>Product PackSizes will adjust accordingly</i>)

Field	Mandatory	Limit	Uses default if blank	Comment
Header Fields				
FromArea	Yes	10		Sending Stock From Branch Code
ToArea	Yes	40		Sending Stock To Branch Code
Status		1		Status: R = Request (<i>default</i>) / T = In Transit / F = Finalised
Name		40	Yes	From Branch Name
Address1		40	Yes	From Branch Address1
Address2		40	Yes	From Branch Address2
Address3		40	Yes	From Branch Address3
DelNme		40	Yes	To Branch Name
DelAd1		40	Yes	To Branch Delivery Address1
DelAd2		40	Yes	To Branch Delivery Address2
DelAd3		40	Yes	To Branch Delivery Address3
OrderNo		20		Order Number
Reference		10		Reference Number
Salesman		6		Salesman Code
Courier		20		Courier Name
ConNote		20		Con Note Number
Cartons		20		Number of Cartons
PackedBy		10		Staff member in charge of Packing Goods
CheckedBy		10		Staff member in charge of Checking Goods
InvoicedBy		10		Staff member in charge of Finalising Goods
Comments		250		Message
Product Fields				
Part	Yes	20		Primary Part Number
Qty	Yes	-		Transfer Qty